

Professional HD-IP 4MP Varifocal Vandal WDR H265 IR Dome Camera



X2C4000VAP

- 4 Megapixel Resolution
- 2.8-12mm (23-92°) Lens
- 30m Smart IR Night Vision
- H265 Video Compression
- PoE Compatible
- Smartphone Remote Access



Features

Professional HD-IP Dome Camera supplied in a vandal resistant dome housing. A high quality 2.8-12 mm varifocal Lens for a 23-92° viewing angle with high power LEDs allowing night vision up to 30 metres.

The 4 Megapixel (2288 x 1712) CMOS Sensor supplied in the X2C4000VAP achieves a resolution approximately 9 times that of a conventional camera. This makes it possible to cover nine times the monitoring area, the image quality being the same. In addition, when captured images are enlarged the detail is much clearer.

Technical Specifications

X2C4000VAP

Brand	XVISION
Model Number	X2C4000VAP
Style	HD Varifocal Dome Camera
Weather Resistant	Yes (IP66 Rated)
Vandal Resistant	Yes
Motorised Panning	No
Motorised Tilting	No
Digital Zoom	No
Audio	No
Mounting Type	Wall or Ceiling
Dimensions (WxHxD) mm	146x101x146
Weight (kg)	0.7
Image Sensor	1/2.9" Sony CMOS
Resolution	4 Megapixel
Minimum Illumination	0.001 Lux
Night Vision	30m
Other Features	Automatic White Balance, Automatic Gain Control, Automatic Electronic Iris DNR (Digital Noise Reduction), WDR (Wide Dynamic Range)
Lens	2.8-12mm
Viewing Angle	23-92°
Video Compression	H265
Video Streams	1024Kbps-6144Kbps
Stream Types	Complex Stream/Video Stream
Resolution & Frame Rates	2288x1712 @25fps
Network Connection	RJ45 Socket (10/100 Base-T)
WiFi Support	No
Network Protocols	TCP/IP, UDP, HTTP, DHCP, RTP/RTSP, DNS, DDNS, NTP, PPPoE, UPNP, SMTP
Browser Support	Internet Explorer
Mobile Phone Support	Android, iPhone
User Authentication	Yes
Simultaneous Viewers	10
Power Over Ethernet	Yes
Operating Voltage	12V DC
Power Consumption	<5W
Easy Fit	Yes (Optional Ethernet Over Mains Adaptor)
Motion Detection	No
Presets	No
Guard Tours	No
Email Alerts	Yes
On-Board Recording	No
Alarms	No
Multi-Camera Software	Yes

All specifications shown are subject to change without notice, please confirm up-to-date details when ordering. All network specifications and recording times are based upon theoretical scenarios. Actual performances will vary depending on external factors. No liability will be accepted by Y3K for any errors or omissions in this information. All relevant trade marks acknowledged. © Y3K (Europe) Limited 2015

■ DISTRIBUTED BY



Xvision (UK)

Unit 2 Valley Point, Beddington Farm Road, Croydon, Surrey, CR0 4WP
Tel: 0208 689 9999 Fax: 0871 222 143 Web: www.xvision.com