

Tamper Resistant Mini HD IP Dome with Power Over Ethernet and ONVIF compliance (Model: X720D)



The X720D is a high definition HD IP Dome camera that offers 4x the resolution of standard CCTV and IP CCTV cameras, perfect for unobtrusive use in premises such as Retail Premises, Restaurants, Bars, Offices and Hotel Lobbies. The camera produces Real Time images at 1.3 Megapixel (1280x960), 720P (1280x720) and D1 (704x576) resolution.

The camera features a compact and tamper resistant design that is perfect for indoor use.

The X720D is ONVIF compliant and is supplied with a powerful multi-camera software for Windows PCs that allows features such as Live Viewing, Playback, Configuration, Multi-Site control and a Push Video function. Additionally the camera can be viewed remotely from a PC, Mac or Mobile Phone.




Camera - Front



Camera - Side



Camera - Rear



Camera - Connections

Specifications

Model: X720D

Image



Type

Style Mini IP Dome Camera with H264 Compression & Power over Ethernet

Weather Resistant No

Vandal Resistant Yes

Motorised Panning No

Motorised Tilting No

Digital Zoom Yes

Audio No

Mounting Type Wall or Ceiling

Product Dimensions (without bracket) Width: 110mm, Height: 54mm, Depth: 110mm

Product Weight 0.25 Kg

Shipping Dimensions Width: 155mm, Height: 115mm, Depth: 155mm

Shipping Weight 0.32 Kg

Warranty 1 Year Warranty (Extendable to 3 years)

Camera

Image Sensor Type 1/3" 1.3 Megapixel Aptina CMOS

Image Sensor Resolution 1,228,800 pixels

Minimum Illumination 0.1 Lux (Colour), 0.05 Lux (B/W)

Night Vision No

Other Features Automatic White Balance
Automatic Gain Control
Automatic Electronic Iris
DNR (Digital Noise Reduction)

Lens 3.6mm

Viewing Angle 78°

Performance

Video Compression H264, MJPEG

Video Streams 11 Independent Streams + 2 Region Of Interest Streams

Stream Types HTTP, RTSP, UDP

Video Resolution & Frame Rates 1.3 Megapixel (1280x960) at up to 15 fps
720P (1280x720) at up to 25 fps
D1 (704x576) at up to 25 fps

Specifications

Model: X720D

Image



Networking

Network Connection	RJ45 Socket (10/100 BASE-T)
Wi-Fi Support	N/A
Network Protocols Supported	HTTP, TCP/IP, IPv4/IPv6, ARP, IGMP, ICMP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, UPNP, NTP, Bonjour, SNMP, Onvif

Remote Access

Browser Support	Chrome, Internet Explorer, Safari
Mobile Phone Support	Android, Blackberry, iPhone, Nokia (Symbian), Windows Mobile
User Authentication	User Name & Password, IP Filtering
Simultaneous Viewers	Using Unicast: 20 Using Multicast: Unlimited

Power Requirements

Power over Ethernet	Yes
Operating Voltage	12V DC
Power Consumption	<1.5W

Other Features

Easy Fit	Optional Xvision Ethernet over Mains adaptor required
Motion Detection	Yes
Presets:	N/A
Guard Tours	N/A
Email Alerts	Yes
On Board Recording	Yes
Alarms	N/A
Multi Camera Software	Yes