

HD 1080P

Professional Hybrid (HD 1080P, 960H) Vandal WDR Micro IR Dome Camera







XHC1080M

- Full HD 1080P & HD 960H Resolution
- 2.8mm (92°) Lens
- 15m Smart IR Night Vision
- Advanced Wide Dynamic range
- · High-speed Digital Slow Shutter
- 3D Digital Noise Reduction
- Weatherproof (IP66 Rated)





Version 1 www.xvision.com

Features

A micro-sized High Definition Vandal Resistant IR Dome camera ideal for use in porches or alleyways where too much IR causes distortion to your night time recordings.

The XHC1080M Hybrid Dome Camera allows you the option of Full HD 1080P resolution image or a 960H Conventional 1000 TVL image enclosed in a discreet dome enclosure giving you the ultimate flexibility on installation. The camera is suitable for indoor or outdoor use and is supplied with a very wide angle 2.8mm Megapixel lens with its Full High Definition image and miniature size and features energy efficient Infrared LEDs for up to 15 metres night vision in complete darkness.

The XHC1080M features a powerful Xvision X3K-DSP which process the image in real time, in addition to this the camera features Digital Noise Reduction (3x DNR) which will remove pixelation and noise from the camera picture in low-light conditions, resulting in a clearer image and reduction in recording space when used with a DVR and Wide Dynamic Range (WDR) to produce an even image that does not suffer from bright or dark spots.

Technical Specifications

XHC1080M

XVISION Brand Model Number XHC1080M Micro Dome Camera Style Weather Resistant Yes (IP66) Vandal Resistant Wall or Ceiling Mountina Type Dimensions (WHD in mm) 60x58x60 Weight (kg) 0.17 Warranty 1 Year Warranty 1/2.8" Sony 2.43 Megapixel CMOS Sensor Type Xvision X3K DSP

DSP Type

Sens-up, Wide Dynamic Range, Noise Reduction, Defog, DPC, Mirror DSP Functions MD, Privacy Zone, Automatic Gain Control, White Balance

HD 1080P (AHD 2.0) / AHD 720P / HD 960H (Analogue) Resolution

Minimum Illumination 0.0003 Lux (0 Lux IR On) Night Vision 15m

Lens Type Fixed Lens Size 2.8mm Viewing Angle 92° 12v DC Operating Voltage Suggested Power Supply 12v DC 1250mA Video Output **BNC Socket** Audio Output No DC Socket Power Input RS485 Control Nο

All specifications shown are subject to change without notice, please confirm up-to-date details when ordering. All network specifications and recording times are based upon theoretical scenarios.

Actual performances will vary depending on external factors. No liability will be accepted by Y3K for any errors or omissions in this information. All relevant trade marks acknowledged. © Y3K (Europe) Limited 2015