Full HD Bullet IP Camera with On Board SD Card Slot, 30m IR Night Vision and ONVIF compliance

(Model: XP3000B)

The XP3000B is a high definition IP Bullet camera that offers 10x the resolution of standard CCTV and IP CCTV cameras, perfect for use inside or outside any premises requiring a very high resolution IR night vision capable camera. The camera produces Real Time images at 1080P (1280x960), 720P (1280x720) and D1 (704x576) resolution.

The camera has advanced DSP functions allowing it to cope with a wide variety of extreme lighting conditions, like car headlights, making it ideal for Number Plate Recognition up to a maximum range of up to 8m.

The XP3000B is ONVIF compliant and is supplied with a powerful multi-camera software for Windows PCs that allows features such as Live Viewing, Playback, Configuration, Multi-Site control and a Push Video function. Additionally the camera can be viewed remotely from a PC, Mac or Mobile Phone.

Camera - Front

Camera - Side

Camera - Rear

Camera - Connections

Specifications

Model: XP3000B	
Image	
Type	
Style	Full HD IP Bullet Camera
Weather Resistant	Yes (IP 66 rated)
Vandal Resistant	No
Motorised Panning	No
Motorised Tilting	No
Digital Zoom	No
Audio	Yes
Mounting Type	Wall or Ceiling (optional bracket required)
Product Dimensions (without bracket)	Width: 101mm, Height: 118.3mm, Depth: 288mm
Product Weight	2.5Kg
Shipping Dimensions	Width: 360mm, Height: 175mm, Depth: 175mm
Shipping Weight	2.76 Kg
Warranty	1 Year Warranty (Extendable to 3 years)
Camera	
Image Sensor Type	1/2.8" 3.0 Megapixel Progressive Scan Exmor CMOS
Image Sensor Resolution	3,271,856 pixels
Minimum Illumination	0.2 Lux (Colour), 0 Lux (B/W), 0 Lux (IR on)
Night Vision	Up to 30m
Other Features	Automatic White Balance Automatic Gain Control Automatic Electronic Iris DNR (Digital Noise Reduction) True Day/Night Number Plate Recognition (8m)
Lens	8 to 16mm
Viewing Angle	17 to 35°
Performance	
Video Compression	H264, MJPEG
Video Streams	11 Independent Streams + 2 Region Of Interest Streams
Stream Types	HTTP, RTSP, UDP
Video Resolution & Frame Rates	3 Megapixel (2048x1536) at up to 15 fps 1080P (1920x1080) at up to 25fps 720P (1280x720) at up to 25 fps D1 (704x576) at up to 25 fps

© Copyright Xvision 2012- Version 1.0

Specifications

Model: XP3000B	
Image	
Networking	
Network Connection	RJ45 Socket (10/100 BASE-T)
Wi-Fi Support	N/A
Network Protocols Supported	HTTP, TCP/IP, ICMP, RTSP, RTP, UDP, SMTP, NTP, DHCP, DNS, DDNS, PPPOE, IP Filter, FTP, Alarm Server
Remote Access	
Browser Support	Chrome, Internet Explorer, Safari
Mobile Phone Support	Android, Blackberry, iPhone, Nokia (Symbian), Windows Mobile
User Authentication	User Name & Password, IP Filtering
Simultaneous Viewers	Using Unicast: 20 Using Multicast: Unlimited
Power Requirements	
Power over Ethernet	Yes
Operating Voltage	12V DC/ 24V AC
Power Consumption	<15W
Other Features	
Easy Fit	Optional Xvision Ethernet over Mains adaptor required
Motion Detection	Yes
Presets	N/A
Guard Tours	N/A
Email Alerts	Yes
On Board Recording	Yes
Alarms	N/A
Multi Camera Software	Yes

© Copyright Xvision 2012 - Version 1.0