

Model: XS1080BP4 Professional HD (1080P) 4 Camera IR Bullet IP CCTV System



XC1080BP



XRN0808E

A FULL HD 1080P resolution Professional IP CCTV kit, supplied ready to fit and complete with a simple to use Professional Mini NVR for viewing, recording and managing the cameras.

This complete kit is ideal for anyone looking for a Professional FULL HD IP CCTV system, comprising of 4 Professional grade IP cameras and a simple to use NVR, the kit is excellent value for money.

Included in the package is an Xvision Pro HD XRN0808E NVR, which will record and display the cameras in FULL 1080P High Definition. The NVR is as easy to use as a DVR, and can be controlled by a USB Mouse. It is fully networkable and can be accessed from all popular mobile phones, recordings can be made on an external USB hard Drive up to 2TB (Not Supplied).

The cameras provided with the system are Xvision Pro HD XC1080BP IP Bullet cameras, offering Full HD 1080P resolution for excellent image quality - twice that of SKY HD and 720P HD IP cameras. They are Tamper Resistant with a cable managed bracket, designed for indoor or outdoor use and fitted with a wide angle lens.

The cameras are PoE compatible and a PoE switch is provided, PoE makes installation simple, as the data and power are sent through the network cable. The camera is designed to be tamper proof and is compact and stylish, making it ideal for use in all types of premises.

Detailed easy to follow DIY fitting instructions are included, if you do need assistance we have a team of friendly professional technicians at the the end of the phone waiting to help.

Features

- CCTV system with 4 cameras and 8 camera recorder for future expansion
- DIY Installation
- Connect the recorder and cameras to the POE switch included - cameras are powered via the network cables included!
- Maximum resolution of 1280x1080 at 30fps
- Xvision 3.6mm HD megapixel lens for 78° viewing angle
- Xvision X3K-IP DSP
- 0.0003 lux low light level
- Up to 30m Smart IR Night Vision
- IP66 Rated
- DVR recording rate 720/1080P: 240fps real time (30fps per camera)
- Remote access via Smartphone, Tablet, PC and Mac
- Email Alerts
- VGA and HDMI Monitor outputs
- 100MB Lan connection
- Plug and play external recording via ESATA or USB
- Estimated recording space required per camera per day: 130GB at 1080P and 30fps, 43GB at 1080P and 10fps, 58GB at 720P and 30fos and 19GB at 720 and 10fps.

Kit comes with:

- 4 cameras (XC1080BP)
- 1 POE Switch with 4 POE ports + 4 standard ports (XIPPOESW-8)
- 1 Recorder (XRN0808E)
- 4 x 30m Network cables (SD30P)
- 1 x 3m Network cable (SD03P)

Camera Specifications

Model Number	XS1080BP
Style	High Definition Bullet Camera
Weather Resistant	Yes (IP66)
Vandal Resistant	No
Mounting Type	Wall or Ceiling
Dimensions	66x66x167
Weight (Kg)	0.4
Warranty	1 Year Warranty (extendable to 3 years)
Sensor Type	1/2.9" Sony CMOS
DSP Type	XVISION 1K IP
DSP Functions	Automatic White Balance Automatic Gain Control Automatic Electronic Iris DNR (Digital Noise Reduction)
Resolution	1080P
Minimum Illumination	0.003 Lux (0 Lux IR On)
Night Vision	20/30m IR Night Vision
Lens Type	Fixed
Lens Size	3.6mm
Viewing Angle	78°
Operating Voltage	12V DC
Suggested Power Supply	12V DC 1250mA
Audio Output	N/A
Power Input	DC Socket
RS485 Control	No
NVR	
Model Number	XRN0808E
Video Compression	H.264
Video System	NTSC / PAL
Video Input / Output	8CH 720P/1080P
Spot Output	No
Audio Input / Output	IPC Complex audio input
Display Resolution	VGA/HDMI sync output, 1920×1080, 1440×900, 1280×1024, 1366×768, 1024×768, 800×600
Display Feature	Single, Quad, S.E.Q
Recording Resolution	1920x1080P
Recording Speed	25fps (Each Ch)
Recording Mode	Continuous, Manual, Motion Detection
Playback Channel	1 / 4 Ch
Playback Speed	25fps (Each Ch)

NVR	
DVD-RW	No
Sensor & Alarm I/O	No
ESATA	1 only for backup
Network	Lan, DHCP, Dynamic IP & DDNS
HDD Interface	USB, ESATA
Multiplex Operation	Live Display, Record, Playback, backup and Network
USB	USB (For mouse and backup Network)
PTZ Control	Yes
Mobile Surveillance	Goolink
CMS Software	64 CH, 256 pcs DVR, no limit to users
Web Browser	Windows: Internet Explorer Mac: Safari, Chrome, Firefox
VGA	800*600, 1024*768, 1280*1024, 1440*900, 1920*1080
HDMI	1920X1080P
Power Supply	DC 12V 2000mA
Fan	2x Case (40x40mm), 1x CPU (40x40mm)
On/Off Switch	Yes
Remote Control	Yes
Rack Mount Size in (U)	N/A
Housing Dimensions	88x88x32mm