

## Model: XS720VP4 Professional HD (720P) 4 Camera IR Dome IP CCTV System



XC720VP



XRN0808E

A HD 720P resolution 4 Camera IP CCTV kit, supplied ready to fit and complete with a simple to use Mini NVR for viewing, recording and managing the cameras.

This complete kit is ideal for anyone looking for a Professional FULL HD IP CCTV system, comprising of 4 Professional grade IP cameras and a simple to use NVR, the kit is excellent value for money.

Included in the package is an Xvision Pro HD XRN0808E NVR, which will record and display the cameras in HD720P High Definition. The NVR is as easy to use as a recorder, and can be controlled by a USB Mouse. It is fully networkable and can be accessed from all popular mobile phones, recordings can be made on an external USB Hard Drive up to 2TB (Not Supplied)

The cameras provided with the system are Xvision Pro HD XC720VP IP Dome cameras, offering HD 720P resolution for excellent image quality. They are Tamper Resistant with a cable managed bracket and designed for indoor or outdoor use.

The cameras are PoE compatible and a PoE switch is provided, PoE makes installation simple, as the data and power are sent through the network cable. The camera is designed to be tamper proof and is compact and stylish, making it ideal for use in all types of premises.

Detailed easy to follow DIY fitting instructions are included, if you do need assistance we have a team of friendly professional technicians at the the end of the phone waiting to help.

## Features

- HD CCTV system with 4 cameras and 8 camera recorder for future expansion
- DIY Installation
- Connect the recorder and cameras to the POE switch included - cameras are
- Powered via the network cables included!
- Maximum resolution of 1280x720 at 30fps
- Xvision 3.6mm HD megapixel lens for 60° viewing angle
- Xvision X1K-IP DSP
- 0.001 lux low light level
- Up to 30m Smart IR Night Vision
- IP66 Rated
- DVR recording rate 720/1080P: 240fps real time (30fps per camera)
- Remote access via Smartphone, Tablet, PC and Mac
- Email Alerts
- VGA and HDMI Monitor outputs
- 100MB Lan connection
- Plug and play external recording via ESATA or USB
- Estimated recording space required per camera per day: 120GB at 1080P and 30fps, 43GB at 1080P and 10fps, 58GB at 720P and 30fos and 19GB at 720 and 10fps.

### Kit comes with:

- 4 cameras (XC720VP)
- 1 POE Switch with 4 POE ports + 4 standard ports (XIPPOESW-8)
- 1 Recorder (XRN0808E)
- 4 x 30m Network cables (SD30P)
- 1 x 3m Network cable (SD03P)

### Camera Specifications

<b>Model Number</b>	XS720V
<b>Style</b>	High Definition EyeBall Dome
<b>Weather Resistant</b>	Yes (IP66)
<b>Vandal Resistant</b>	Yes
<b>Mounting Type</b>	Wall or Ceiling
<b>Dimensions</b>	93x83.3x93
<b>Weight (Kg)</b>	0.3
<b>Warranty</b>	1 Year Warranty (extendable to 3 years)
<b>Sensor Type</b>	1/4" OV CMOS
<b>DSP Type</b>	XVISION 1K IP
<b>DSP Functions</b>	Automatic White Balance Automatic Gain Control Automatic Electronic Iris DNR (Digital Noise Reduction)
<b>Resolution</b>	720P
<b>Minimum Illumination</b>	0.001 Lux (0 Lux IR On)
<b>Night Vision</b>	20/30m IR Night Vision
<b>Lens Type</b>	Fixed
<b>Lens Size</b>	3.6mm
<b>Viewing Angle</b>	60°
<b>Operating Voltage</b>	12V DC
<b>Suggested Power Supply</b>	12V DC 1250mA
<b>Video Output</b>	RJ45
<b>Audio Output</b>	N/A
<b>Power Input</b>	DC Socket
<b>RS485 Control</b>	No
<b>NVR</b>	
<b>Model Number</b>	XRN0808E
<b>Video Compression</b>	H.264
<b>Video System</b>	NTSC / PAL
<b>Video Input / Output</b>	8CH 720P/1080P
<b>Spot Output</b>	No
<b>Audio Input / Output</b>	IPC Complex audio input
<b>Display Resolution</b>	VGA/HDMI sync output, 1920×1080, 1440×900, 1280×1024, 1366×768, 1024×768, 800×600
<b>Display Feature</b>	Single, Quad, S.E.Q
<b>Recording Resolution</b>	1920x1080P
<b>Recording Speed</b>	25fps (Each Ch)
<b>Recording Mode</b>	Continuous, Manual, Motion Detection
<b>Playback Channel</b>	1 / 4 Ch
<b>Playback Speed</b>	25fps (Each Ch)

NVR	
DVD-RW	No
Sensor & Alarm I/O	No
ESATA	1 only for backup
Network	Lan, DHCP, Dynamic IP & DDNS
HDD Interface	USB, ESATA
Multiplex Operation	Live Display, Record, Playback, backup and Network
USB	USB (For mouse and backup Network)
PTZ Control	Yes
Mobile Surveillance	Goolink
CMS Software	64 CH, 256 pcs DVR, no limit to users
Web Browser	<b>Windows:</b> Internet Explorer <b>Mac:</b> Safari, Chrome, Firefox
VGA	800*600, 1024*768, 1280*1024, 1440*900, 1920*1080
HDMI	1920X1080P
Power Supply	DC 12V 2000mA
Fan	2x Case (40x40mm), 1x CPU (40x40mm)
On/Off Switch	Yes
Remote Control	Yes
Rack Mount Size in (U)	N/A
Housing Dimensions	88x88x32mm