



VEHICLE JOURNEY RECORDER

Quick Guide

STEP 1: WHAT'S IN THE BOX?

SVC100GPS

- SVC100GPS Camera /Recording Unit including bracket
- Wire Splice Clips
- Set of stickers for Windscreen Mounting (Double-sided Tape x 2)
- Power Cable (Cigarette Jack)
- USB 2.0 SD Card Reader
- Spare Mounting Bracket
- SD Memory Card*
* SD Card size will depend on the model and may not be included.

SVC100GPS-LCA-LCA2

Item contains all accessories on the left, plus the following;

- Transparent Locking Case
- Keys for Locking Case
- Telematics Cable

Please note: The SVC100GPS-LCA2 will have an extra alarm output wire

STEP 2: INSERT SD CARD

Please Note

If you have been supplied with an SD card, then this will need to be set-up using the latest Smart Witness software.

1. This software can be downloaded from www.smartwitness.co.uk/article/76/support

Once on the page, select the correct software by using the Drop Down Menu



Our latest Datasheets, Manuals, Software are available here for download

1) Select Datasheets, Manuals, Software or Firmware
Software

2) Select Product Model
SVC100GPS

DOWNLOAD


2. When downloaded, go to the 'Downloads' folder and double click the 'setup' file.
3. Follow the set-up instructions, then the software icon will appear on your desktop.

4. Double click the software icon to load the software. (Below)




5. Click the 'Tool' button

6. Select the "SD Card Intilise" button from the drop down menu




7. You will presented with another drop down list to select the Card to format.

8. Select the "DRIVERREC" from the drop down and tick the "Quick Format" box when prompted.



9. Click "Start" to begin formatting.

10. Once the card has been formatted, you will see the screen on the right. Then, remove the SD Card from the computer.



11. Make sure the unit is turned off before inserting the SD Card.

12. Insert the SD memory card into the SD card slot.



Please Note

The very first time you power up your unit with the SD Card inserted, it is important not to disconnect the power before the 2 minutes are up, as this may damage the unit.

STEP 3: INSTALLATION

SVC100GPS

- Designed for DIY Fitting

1. Attach the double-sided adhesive tape to the unit.



2. Secure the SVC100GPS to the windscreen behind the rear view mirror. Please make sure that the surface is clean and dry before attaching.



Tip:
Hold in position with firm pressure for 30 Seconds

3. Adjust camera view and make sure the lens has an unobstructed view.



4. Arrange the power cord neatly alongside the windshield and door pillar trim. Use the provided wire splice clip.



5. Connect the SVC100GPS to the cigarette lighter socket.



SVC100GPS-LCA/LCA2

- Professional Installation Recommended

Please don't attempt to permanently wire this unit unless you are familiar with auto wiring.

Any incorrect installations will not be covered by the warranty.



For a full wiring description, please see the manual.

STEP 4: LED Guide



See the table below for an explanation of the LED status changes on the back of the recorder.

No.	BLUE LED	RED LED	Meaning
1	Blink every half second	OFF	Event Recording
2	Blink every 4 Seconds	OFF	Continuous Recording
3	SOLID	OFF	Pre-Recording (Awaiting Triggers)
4	OFF	Blink every half second	Card Fault
5	SOLID	SOLID	System Booting Up
6	Blink every half second	Blink every half second	Unit Fault
7	SOLID	OFF	SD Card Removal in Safe Mode
8	OFF	OFF	No Power

SAFE SD CARD REMOVAL

To remove the SD card either:

- Disconnect the power to the unit, wait until all LEDs are off and then remove the card.
- Use SAFE MODE. To enter safe mode whilst the unit is powered and in recording mode, press the “SD Card Format” (Blue) button for 3 seconds until the unit beeps to acknowledge it is in safe mode, then remove the SD card.